

Description

xFORM D is a multifunctional product that delivers viscosity, hole cleaning and fluid loss control. xFORM D is a simple to use powder product that will help improve drilling efficiency by improving hole cleaning and fluid loss control.

Application

While xFORM D is highly dispersible and therefore well suited to be used where minimal agitation exists, where possible, it should be added via a hopper and allowed the blend in prior to use.

Typical Physical Properties

Appearance:	White to off white powder
Solubility in water:	Soluble

Recommended Treatment

Typical concentrations for xFORM D range from 1 – 4kg / m³. If chlorides are more than 10,000mg / L or total hardness is more than 500mg/L the viscosity yield of xFORM D will be reduced and the required dosage will need to be increased to achieve the desired properties.

Advantages

- Reduces rod chatter
- Simplifies workflows – one product to add in place of multiple
- Suitable for use in all water types
- Disperses readily into the mix tank
- Eliminates drilling fluid product waste due to poor mixing



Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest IMDEX AMC representative for optimum results.

ASIA PACIFIC

Perth, Australia (Head Office)
+61 8 9445 4000

Indonesia
+61 (0) 21 759 11244

AFRICA

South Africa
+27 (11) 908 5595

EUROPE

Norway
+47 72 87 01 01

Germany
+49 4402 9650-0

United Kingdom
+44 (0) 1273 483 700

SOUTH AMERICA

Argentina
+54 9 261 211 3676

Brazil
+55 (47) 3404 5920

Chile
+56 (2) 2589 9300

Peru / Ecuador
+51 (1) 322 8850

NORTH AMERICA

USA / Canada
+801-364-0233

Mexico
+52 (871) 680 7146