

# AMC COPPER COMPOUND™

Lubricants &amp; Cutting Oils



## Description

COPPER COMPOUND™ is a high quality, non-melt, anti-seize thread compound containing solid lubricants to ensure outstanding lubrication and high temperature resistance.

COPPER COMPOUND™ is designed to prevent galling, it protects threads from wear, tear and seizing. COPPER COMPOUND™ will not evaporate when exposed to extreme high temperatures. COPPER COMPOUND™ contains anti-rust agents, is wash resistant, will operate under extreme pressures and is lead free.

## Application

COPPER COMPOUND™ should be applied generously to the tool joints and threaded sections of the drill pipe with a brush, spatula or any other suitable item. COPPER COMPOUND™ is extremely tenacious and will adhere to all metal surfaces.

## Recommended Treatment

Applied generously to the tool joints and threaded sections of drill pipe before connecting.

*Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest AMC representative for optimum results.*

## Advantages

- Easily applied
- Prevents seizing
- Resistant to extreme high temperature
- Provides good electrical and thermal conductivity properties
- Minimises wear
- Aids in preventing corrosion to applied areas

## Typical Physical Properties

Appearance:	Gold bronze semi-solid paste
Solubility in water:	Extremely high melting point

### ASIA PACIFIC

Perth, Australia (Head Office)  
+61 8 9445 4000

Indonesia  
+61 (0) 21 759 11244

### AFRICA

South Africa  
+27 (11) 908 5595

### EUROPE

Norway  
+47 72 87 01 01

Germany  
+49 4402 9650-0

United Kingdom  
+44 (0) 1273 483 700

### SOUTH AMERICA

Argentina  
+54 9 261 211 3676

Brazil  
+55 (47) 3404 5920

Chile  
+56 (2) 2589 9300

Peru / Ecuador  
+51 (1) 322 8850

### NORTH AMERICA

USA / Canada  
+801-364-0233

Mexico  
+52 (871) 169 2095