

AMC SUPERLUBE™

Lubricants & Cutting Oils



Description

SUPERLUBE™ is a vegetable oil based lubricant which was developed specifically for the mineral exploration industry. Its ideally suited for the operating parameters at the bit face giving improved bit life and penetration rates.

Application

SUPERLUBE™ is readily miscible in make up water meaning little agitation is required when adding it to the mud system. It will form a protective coating on the metal surfaces reducing torque and frictional drag on the drill rods, minimizes wear on the drill string rods, barrel and inner tubes.

Recommended Treatment

Application	kg/m ³
To reduce vibration and torque	2.5 – 5
To improve bit life in extremely hard and abrasive ground	5 – 10

Advantages

- Produces a thin protective film on the metal surfaces
- Reduces torque
- Improves rod, bit and reamer life
- Improves penetration rates
- Will not contribute to core staining
- Environmentally acceptable

Typical Physical Properties

Appearance:	Clear, light to dark amber liquid
pH:	7.0 - 9.5
Specific gravity:	0.85 - 1.0
Solubility in water:	Miscible

Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest AMC representative for optimum results.

ASIA PACIFIC

Perth, Australia (Head Office)
+61 8 9445 4000

Indonesia
+61 (0) 21 759 11244

AFRICA

South Africa
+27 (11) 908 5595

EUROPE

Norway
+47 72 87 01 01

Germany
+49 4402 9650-0

United Kingdom
+44 (0) 1273 483 700

SOUTH AMERICA

Argentina
+54 9 261 211 3676

Brazil
+55 (47) 3404 5920

Chile
+56 (2) 2589 9300

Peru / Ecuador
+51 (1) 322 8850

NORTH AMERICA

USA / Canada
+801-364-0233

Mexico
+52 (871) 169 2095