

# EUROGEL XTRA™

Viscosifiers



## Description

EUROGEL XTRA™ is a high yield bentonite that provides excellent hole cleaning and filtration control properties while also providing some viscosity.

## Application

EUROGEL XTRA™ is ideally suited for use in horizontal directional drilling, water well, mining and tunnelling applications. EUROGEL XTRA™ should be added through a hopper and allowed to mix for 10 – 15 minutes so that the product can fully yield prior to use. EUROGEL XTRA™ yield and time to achieve maximum yield are adversely affected by water quality.

## Recommended Treatment

Application	kg/m <sup>3</sup>
Normal drilling conditions	15 – 25
Sandy formations	25 – 35
Unconsolidated formations	30 – 40

*Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest AMC representative for optimum results.*

## Advantages

- Twice the yield of API grade bentonites
- Rapid yielding
- Provides excellent hole cleaning
- Enhances fluid loss control
- Assists in borehole stabilisation

## Typical Physical Properties

Appearance:	Greenish, tan powder
Solubility:	Insoluble in water
Specific gravity:	2.3 – 2.6
pH (2.5% solution):	7.5 – 9.5

### ASIA PACIFIC

Perth, Australia (Head Office)  
+61 8 9445 4000

Indonesia  
+61 (0) 21 759 11244

### AFRICA

South Africa  
+27 (11) 908 5595

### EUROPE

Norway  
+47 72 87 01 01

Germany  
+49 4402 9650-0

United Kingdom  
+44 (0) 1273 483 700

### SOUTH AMERICA

Argentina  
+54 9 261 211 3676

Brazil  
+55 (47) 3404 5920

Chile  
+56 (2) 2589 9300

Peru / Ecuador  
+51 (1) 322 8850

### NORTH AMERICA

USA / Canada  
+801-364-0233

Mexico  
+52 (871) 169 2095