

# AMC CEMENT PLUGS™

Drilling fluids equipment



## Description

Displacement plugs are used in diamond wireline drill rods and casings for placing cement plugs or casing pack fluid.

## Application

Commonly used for cleaning the inside of drilling rod and indicators during cementing or grouting operations. Place plug in drill rods in front of cement slurry as an indicator.

Then place plug behind cement slurry, this will wipe excess slurry from rod walls.

## Advantages

- Made from natural soft rubber

PQ plug -  
180x105mm



HQ plug -  
105x80mm



NQ plug -  
65x65mm



### ASIA PACIFIC

Perth, Australia (Head Office)  
+61 8 9445 4000

Indonesia  
+61 (0) 21 759 11244

### AFRICA

South Africa  
+27 (11) 908 5595

### EUROPE

Norway  
+47 72 87 01 01

Germany  
+49 4402 9650-0

United Kingdom  
+44 (0) 1273 483 700

### SOUTH AMERICA

Argentina  
+54 9 261 211 3676

Brazil  
+55 (47) 3404 5920

Chile  
+56 (2) 2589 9300

Peru / Ecuador  
+51 (1) 322 8850

### NORTH AMERICA

USA / Canada  
+801-364-0233

Mexico  
+52 (871) 680 7146