

AMC HEXA T™

Flocculants & Dispersants

IMDEX™

Description

HEXA T™ is a fast-acting dispersant that will assist in breaking up the wall cake that has formed on the walls of the drill hole, promoting rapid and effective clean up. AMC HEXA T™ can be used in the clean up and development of bore holes where bentonite-based mud has been used and can also act as a deflocculated. HEXA T™ also has anti scaling properties.

Application

Calculate the volume of fluid inside the well. Calculate the total amount of HEXA T™ required to achieve the desired dosage for the whole well and dissolve this amount in a suitably sized container of water. Circulate the dissolved HEXA T™ through the well, homogenizing it along the whole fluid column, circulating for 30 minutes. Leave the product to act in the well for at least 6 hours then circulate the fluid again to displace.

Recommended Treatment

Typical dosages range from 3 – 10 kg / m³.

Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest AMC representative for optimum results.

Advantages

- Helps removes wall cake and solids build up
- Helps removes built up polymers like PAC and PHPA
- Aids in treating Calcium and Magnesium hardness
- Aids in preventing calcium scale

Typical Physical Properties

Appearance:	White to off white powder
Solubility in water:	Soluble
pH (1% solution):	6 - 8

ASIA PACIFIC

Perth, Australia (Head Office)
+61 8 9445 4000

Indonesia
+61 (0) 21 759 11244

AFRICA

South Africa
+27 (11) 908 5595

EUROPE

Norway
+47 72 87 01 01

Germany
+49 4402 9650-0

United Kingdom
+44 (0) 1273 483 700

SOUTH AMERICA

Argentina
+54 9 261 211 3676

Brazil
+55 (47) 3404 5920

Chile
+56 (2) 2589 9300

Peru / Ecuador
+51 (1) 322 8850

NORTH AMERICA

USA / Canada
+801-364-0233

Mexico
+52 (871) 169 2095