AMC PVC MUD MIXER HEAVY DUTY™

Drilling fluids equipment



Description

The AMC PVC MUD MIXER HEAVY DUTY™ is a Venturi mixing apparatus for drilling applications.

Installation

- Mount the AMC PVC MUD MIXER HEAVY DUTY over the selected mix tank, face discharge downwards with the discharge well clear of the high fluid level.
- Use gate or ball valve. Connect to 25 mm (1 inch minimum) water line.

Safe Operating Procedures

- Ensure that the mixers are not blocked prior to mounting onto the mix tanks.
- Ensure that the mixer is not fully closed prior to starting the mixing pump.
- Do not exceed 150 psi pump pressure through the mud mixer.



^{*}Plastic or stainless steel

Operation

- Turn on water.
- Insert product suction line gently, approximately 6 -8mm (¼ inch) into the polymer powder to lift a mixture of air and polymer.
- To increase flow rate through AMC PVC MUD MIXER HEAVY DUTY increase pump volume output or adjust locking coupling on unit. Unscrewing the coupling assembly will increase flow through unit, tightening the coupling assembly will decrease flow through the unit.

Do not over-tighten the locking coupling. Unscrewing the coupling too far whilst pump is operating will cause the insert section to come out, wetting product and operator.

Cleaning

- If the mixer blocks, remove product suction line from unit.
- Wash the unit with fresh water until clean.
- 3. Dry thoroughly with air and a clean rag. DO NOT use solvents.
- Completely unscrew the coupling assembly and inspect the o-ring for damage and clean. Lubricate the o-ring prior to assembly.

| Materials | Polyvinyl chloride |
|----------------------------|--|
| Water connection | ¾ inch BSB spigot |
| Recommended suction line | 1 m long x 20 mm clear plastic tubing |
| Minimum water requirements | 100 - 150 litres per minute at 20 psi |
| Nominal lift | 1.2 metre maximum |
| Lift rate | 1 – 1.5 kg per minute |
| | |

Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest IMDEX representative for optimum results.

ASIA PACIFIC

Perth, Australia (Head Office) +61 8 9445 4000 Indonesia +61 (0) 21 759 11244

AFRICA

South Africa +27 (11) 908 5595

EUROPE

Norway +47 72 87 01 01 Germany +49 4402 9650-0 United Kingdom +44 (0) 1273 483 700

SOUTH AMERICA

Argentina +54 9 261 211 3676 Brazil +55 (47) 3404 5920 Chile +56 (2) 2589 9300 Peru / Ecuador +51 (1) 322 8850

NORTH AMERICA

USA / Canada +801-364-0233 Mexico +52 (871) 680 7146

