xFORM™



Description

xFORM D+ is a premium, multifunctional product that delivers viscosity, hole cleaning and fluid loss control. xFORM D+ is a simple to use powder product that will help improve drilling efficiency by improving hole cleaning and fluid loss control.

Application

While xFORM D+ is highly dispersible and therefore well suited to be used where minimal agitation exists, where possible, it should be added via a hopper and allowed the blend in prior to use.

Typical Physical Properties

Appearance: White to off white powder

Solubility in Soluble

water:

Recommended Treatment

Typical concentrations for xFORM D+ range from 1.5 -4kg / m³. If chlorides are more than 10,000mg / L or total hardness is more than 500mg/L the viscosity yield of xFORM D+ will be reduced and the required dosage will need to be increased to achieve the desired properties.

Advantages

- Reduces rod chatter
- Simplifies workflows one product to add in place of multiple
- Suitable for use in all water types
- Disperses readily into the mix tank
- Eliminates drilling fluid product waste due to poor mixing



Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest IMDEX AMC representative for optimum results.

ASIA PACIFIC

Perth, Australia (Head Office) +61 8 9445 4000 Indonesia +61 (0) 21 759 11244

AFRICA

South Africa +27 (11) 908 5595

EUROPE

Norway +47 72 87 01 01 Germany +49 4402 9650-0 United Kingdom +44 (0) 1273 483 700

SOUTH AMERICA

Argentina +54 9 261 211 3676 Brazil +55 (47) 3404 5020 Chile +56 (2) 2589 9300 Peru / Ecuador +51 (1) 322 8850

NORTH AMERICA

USA / Canada +801-364-0233 Mexico +52 (871) 680 7146

